

## RJ45 connector - CUC-V04-RJ45-POBK-8 - 1407413

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



RJ45 connector, IP65/IP67, with push/pull interlocking (version 4), plastic housing, for 10 Gbps, for 24 ... 28 AWG stranded conductors

### Why buy this product

- compact design
- IP67 protection class
- Push-pull interlocking



### Key Commercial Data

Packing unit	1 STK
Weight per Piece (excluding packing)	40.000 g
Custom tariff number	85366990
Country of origin	Romania

### Technical data

#### Mechanical characteristics

Standards/specifications	IEC 61076-3-106
Number of positions	8
Connection profile	RJ45
Locking type	Push Pull
Insertion/withdrawal cycles	≥ 750
Connection method	Crimp connection
Type of contact	Crimp contacts
Conductor cross section	stranded
Connection cross section AWG	28 ... 24 (stranded)
Max. cable diameter	4.9 mm ... 8.6 mm

# RJ45 connector - CUC-V04-RJ45-POBK-8 - 1407413

## Technical data

### Mechanical characteristics

External cable diameter	4.9 mm ... 8.6 mm
Cable exit	straight
Color	black

### Ambient conditions

Ambient temperature (operation)	-40 °C ... 70 °C
Ambient temperature (storage/transport)	-40 °C ... 70 °C
Degree of protection	IP65

### Material data

Flammability rating according to UL 94	V0
Housing material	Plastic

### Electrical characteristics


Number of positions	8
Transmission characteristics (category)	CAT6 <sub>A</sub>
GRP transmission properties	CAT6 <sub>A</sub>
Overvoltage category	I
Degree of pollution	2

### Standards and Regulations

Standards/regulations	IEC 61076-3-106
Flammability rating according to UL 94	V0

## Drawings

Dimensional drawing



Dimensional drawing

## Classifications

eCl@ss

eCl@ss 4.0	272607xx
------------	----------

## RJ45 connector - CUC-V04-RJ45-POBK-8 - 1407413

### Classifications

#### eCl@ss

eCl@ss 4.1	27260701
eCl@ss 5.0	27260701
eCl@ss 5.1	27260701
eCl@ss 6.0	27260708
eCl@ss 7.0	27440312
eCl@ss 8.0	27440101
eCl@ss 9.0	27440101

#### ETIM

ETIM 3.0	EC001121
ETIM 4.0	EC001121
ETIM 5.0	EC002636

#### UNSPSC

UNSPSC 6.01	31261501
UNSPSC 7.0901	31261501
UNSPSC 11	31261501
UNSPSC 12.01	31261501
UNSPSC 13.2	31261501

### Approvals

#### Approvals

---

#### Approvals

#### EAC / EAC

---

#### Ex Approvals

---

#### Approval details

EAC EAC-Zulassung
-------------------

EAC B.01742
-------------

## RJ45 connector - CUC-V04-RJ45-POBK-8 - 1407413

Accessories

Accessories

Stripping tool - VS-CABLE-STRIP-VARIO - 1657407

Stripping tool, for the multi-level stripping of shielded cables



---

Phoenix Contact 2016 © - all rights reserved  
<http://www.phoenixcontact.com>